

1U Display / Keyboard / Mouse With Integrated KVM Switch

- Unique design to maximize rack mountable space
- Adjustable mounts for cabinets between 750 -1000mm
- Anodized aluminium front panel
- High quality Cherry keyboard with integrated trackball
- Keyboard options supporting twelve languages
- 15" LCD panel
- Side to side wide-angle viewing as CRT monitor
- On screen display controlled by membrane switches
- Power saving feature for prolonging the lift of LCD panel
- Single D-sub 15-pin inputs for VGA, Mouse and Keyboard
- Build in slide rail and mounts easily in any 19" cabinet
- EMC shielding around the monitor housing to minimize interference



Keyboard

- Integrated, high-quality PS/2 compatible 16mm Logitech trackball
- 84 keys (European layouts), 83 keys (US layout)
- Operating life of individual keys : 20 million operations

KVM Switch

- Built in KVM switch function for easy controlling and monitoring up to 8 residing servers/ platforms
- Support eight characters password protection and search PC server name
- Auto scan mode for monitoring PCs and flexible scan time from 5-99 seconds
- LED display for easy status monitoring
- Supplied with 8 x screened cables, length 6 feet

Computer connections	8
Connector	
Keyboard	6 - pin mini DIN
Mouse	6 - pin mini DIN
Monitor	15 - pin HDD type
Cascade Level	8
Max. access PCs	64
Input VGA Resolution	1,920 x 1,440

Display

15" LCD Monitor	
Display type	TFT / LCD active matrix color
Resolutions	1024 x 768
Response time	Tr =5ms / Tf =20ms
Contrast ratio	300 : 1 typical
Brightness	250 cd/ m ² typical
Pixel pitch	0.297mm (H) x 0.297mm (W)
Panel color	16.7 million display colors
Viewing angle	140°C (Horiz.) / 120°C (Vert.)
Storage temp.	-20°C to 60°C
Operating temp.	0°C to 50°C
MTBF	35,000 hours

Power Supply

- Remote adapter : 110V - 220 V AC Input , 12V 5A Output
- Adapter Size : 10.8 (L) x 6.1 (W) x 3 (H)cm
- Cable length from mains plug to adapter : 182cm
- Cable length from adapter to unit : 180cm
- Safety approval : UL, CE
- Mains plug options available

Optional -48V DC input

Product Dimension

43.9 (W) x 4.45 (H) x 60(D)cm



Westek Technology Limited, Unit 1, Lancaster Park Industrial Estate, Bowerhill, Melksham, Wiltshire, SN12 6TT, UK
PHONE: +44 (0) 1438 745531 FAX: +44 (0) 1225 702968 INTERNET: www.westekuk.com EMAIL: sales@westekuk.com

SPECIFICATION SUBJECT TO CHANGE WITHOUT PRIOR NOTICE