

# LKVM17S LCD KVM Display Drawer

- ▶ Compact 1U 17" LCD KVM Display Drawer
- ▶ 1U Rack Mount Drawer with 17" LCD
- ▶ Integrated Keyboard with Full Numerical Pad
- ▶ Rugged Precision Track Ball Mouse
- ▶ High Resolution 1280 x 1024 Display
- ▶ USB Mouse and Keyboard Interface
- ▶ Various KVM Switch Options Available



Westek Technology's next generation 1U pull out drawer with high quality 17" LCD is a complete solution when an all-in-one monitor, keyboard and mouse is required. Its inbuilt KVM switch makes it ideal for use in racks where it can switch between servers at the press of a button (see following page for options).

Slide rails with fixed positions prevent drawer movement when typing, and an enhanced latching front panel with dual locking points keeps the drawer securely in place.

The drawer is easily mountable in a ~700mm rack and there is a choice of AC or DC power. A VGA I/O is fitted as standard with the option to customise to HDMI or DVI-D.

### 17" LCD Panel Information:

Display pixel	1280 x 1024
Brightness (typ.)	250
Contrast Ratio (typ.)	1000:1
Colour	16.7 M
Viewing Angle (L/R/U/D)	80/80/80/80
Response Time (ms)	5
Dot pitch / Display area (mm)	0.264 / 337.92H x 270.33V
Surface Treatment	Haze 25%, Hard-coating
Surface Hardness	3H
Backlight Type	CCFL

cUL, FCC and CE certified. RoHS2 and REACH compliant.

### Product specification:

- 17" 1280 x 1024 LCD display panel (display area 19" diagonal)
- 0°C to 55°C operating temperature; storage temperature: -20°C to 60°C
- AC 100-240V universal power supply, DC options available
- USB keyboard/mouse. 15-pin VGA or optional D-Sub DVI-D or HDMI
- Full 104-key Qwerty keyboard including 17-key numerical key pad and integrated track ball mouse
- Low power consumption ~40W
- Size: 620 (D) x 441.6 (W) x 44 (H) mm depending on build options
- Weight: ~16kg
- Relative humidity 20~90%, shock 10G 11mSec, vibration 1Grms 5-500Hz

### Westek Technology Ltd

Unit 1 Lancaster Business Park  
Bowerhill  
Melksham  
Wiltshire  
United Kingdom  
SN12 6TT

Tel: +44 (0)1225 790600  
Fax: +44 (0)1225 702968  
E-mail: [sales@westekuk.com](mailto:sales@westekuk.com)  
Web site: [www.westekuk.com](http://www.westekuk.com)

Specifications subject to change without notice

## KVM Switch Options and Ordering Details:

The LKVM17S is available with Matrix DB-15 KVM, Combo DB-15 KVM or a DVI-D KVM.


### Matrix DB-15

Available in 8 and 16 port options with up to two IP ports (IP port requires CAT 5 / 6 cable). Please state at time of ordering if you require the IP option.

Type	Model to Order
Matrix DB-15 8 Port	LKVM17M8
Matrix DB-15 16 Port	LKVM17M16

### Combo DB-15

Available with 8 and 16 ports, this option can also have one IP port (state at time of ordering if IP port required). The Combo DB-15 KVM switch cable can either be 1.8m, 3m or 4.5m - please specify at time of ordering which length is required (1.8m shipped as standard).



Picture shows 16 port Combo option with IP port

Type	Model to Order
Combo DB-15 8 Port	LKVM17C8
Combo DB-15 16 Port	LKVM17C16

### IP Console


Resolution Support	Frequency ( Hz )
1600 x 1200	60
1280 x 1024	60
1024 x 768	60 / 70 / 75

Resolution support for the Matrix DB-15 and Combo DB-15 KVM switches

### DVI-D KVM

Available with 12 ports and either 1.8m or 4.5m CI cable - please specify length required at time of ordering.

Type	Model to Order
DVI-D 12 Port	LKVM17D12



Rear panel of DVI-D 12 port KVM

## Westek Technology Ltd

Unit 1 Lancaster Business Park  
Bowerhill  
Melksham  
Wiltshire  
United Kingdom  
SN12 6TT

Tel: +44 (0)1225 790600  
Fax: +44 (0)1225 702968  
E-mail: [sales@westekuk.com](mailto:sales@westekuk.com)  
Web site: [www.westekuk.com](http://www.westekuk.com)

Specifications subject to change without notice

