

Rugged MIL Portable Rack Case

Shock Mounted 19" Rack Transport Case

- ▶ **4U to 12U Inner 19" Rack Frame**
- ▶ **Tough Roto-Moulded Case with Stainless Steel Rack**
- ▶ **Complies with MIL-STD 810F**
- ▶ **IP65 Sealed with Lids Fitted**
- ▶ **Pressure Equalisation Valve for Air Transport**
- ▶ **Resistant to Most Liquids Including Solvents**
- ▶ **Colour Options Drab Green, Sand and Black**



Available with various standard 19 inch inner frame depth options and with full equipment integration services.

- Eight 'Bi-Angle' elastomeric anti-vibration mounts angled towards centre of gravity of the rack frame, provide optimised shock protection in all orientations.
- Superior 'sway space' between aluminium inner frame and outer case to prevent contact with outer container under severe impact.
- All racks have positive stacking, aligning at the front face regardless of rack depth.
- Internal rack frame conforms to BS5954 / BS EN 60297 / DIN 41494 /ANSI/EIA-310-C .
- Heavy-duty plastic injection moulded handles with soft grip thermo-plastic rubber grips.
- Optional recessed wheels for ease of handling with heavy payloads.
- Optional deeper lids available to accommodate extended/protruding connectors etc.

Part Number	Height	Depth	Width	Rack	Rack Depth	Weight	Wheels	Handles	Catches	Nato Stock Number
	mm	mm	mm	U	mm	Kg	Available			NSN
R0448-0707	328	740	583	4	480	15.4	No	4	12	8145-99-562-6611
R0448-0712	328	795	583	4	480	15.9	Yes	4	12	8145-99-858-1856
R0461-0707	328	870	583	4	610	15.7	No	4	12	8145-99-834-8328
R0461-0712	328	925	583	4	610	16.2	Yes	4	12	8145-99-284-6890
R0648-0707	417	740	583	6	480	16.9	No	4	12	8145-99-989-1224
R0648-0712	417	795	583	6	480	17.3	Yes	4	12	8145-99-896-0886
R0661-0707	417	870	583	6	610	18.9	No	4	12	8145-99-133-7690
R0661-0712	417	925	583	6	610	19.2	Yes	4	12	8145-99-162-8327
R0848-0707	506	740	583	8	480	19.4	No	4	16	8145-99-700-9000
R0848-0712	506	795	583	8	480	19.7	Yes	4	16	8145-99-339-4918
R0861-0707	506	870	583	8	610	21.2	No	4	16	8145-99-862-1593
R0861-0712	506	925	583	8	610	21.5	Yes	4	16	8145-99-742-3340
R1048-0707	595	740	583	10	480	22.1	No	4	20	8145-99-666-7179
R1048-0712	595	795	583	10	480	22.8	Yes	4	20	8145-99-133-7691
R1061-0707	595	870	583	10	610	23.3	No	4	20	8145-99-701-9229
R1061-0712	595	925	583	10	610	24	Yes	4	20	8145-99-509-7384
R1248-0707	684	740	583	12	480	23.2	No	4	20	8145-99-337-7069
R1248-0712	684	795	583	12	480	24.6	Yes	4	20	8145-99-736-7317
R1261-0707	684	870	583	12	610	24.5	No	4	20	8145-99-000-4541
R1261-0712	684	925	583	12	610	25.9	Yes	4	20	8145-99-853-3739



Weight shown above excludes wheel option fitted which adds approximately 1Kg

Westek Technology Ltd
 Unit 1 Lancaster Business Park
 Bowerhill, Melksham
 Wiltshire SN12 6TT
 United Kingdom

Tel: +44 (0)1225 790600
 Fax: +44 (0)1225 702968
 E-mail: sales@westekuk.com
 Web site: www.westekuk.com
 Specifications subject to change without notice